

# Vichy Unique Character Clay Tiles

# Elliotts

Vichy are highly attractive clay plain tiles supplied in three colours: Natural Red, Heather and Antique. The overall dimension of 275mm x 170mm will provide a lap of 70mm which means only 59 tiles are needed per square metre when laid on a 100mm gauge.

Equally at home on new or restored buildings, the Vichy has a longitudinal and cross camber which will enhance the character of any roof.

## Composition and Description

Vichy is a machine made clay tile but with a hand made appearance, resulting from its unique longitudinal and cross camber. Each tile is slightly different in colour adding to the hand made effect, and is fitted with two nibs and two nail holes. Beaver Tail and Club ornamental tiles are also available.

## Applications

The tiles are suitable for residential and commercial purposes and can be fitted to any pitched roof above an angle of 35°.

## Colours

Natural Red, Heather and Antique.

## Accessories and Fittings

A comprehensive range, made to British Standard design, is available, a number of which are illustrated on the leaflet. All stock fittings are suitable for pitch roof angles between 40 degrees and 45 degrees.

## Sitework

Tiles should be fitted in accordance with British Standard Codes of practice BS5534. Part 1:1990 and BS8000:Part 6: 1990. Ridges are laid 3 to a metre (330 mm long) either Half Round or Hogs Back or 2.5 to a metre (450mm long) Angle Ridge. Further information is available from your supplier.

## Ventilation

Requirements can be satisfied by the use of ridge vents, inline tile vents, eaves and dry fix ridge systems. Guidance is given in BS5250, but provision should be made to provide minimum ventilation, equivalent to a continuous opening of 10mm, along two opposite sides of a roof.

## Supply

Tiles and fittings can normally be delivered within two to three weeks from receipt of order. Customers are requested to check availability at time of ordering. Tiles are supplied shrink wrapped on pallets for fork lift unloading to individual order requirements. Average pallet contents 1000 tiles. Crane offload is available, please ask for a quotation.

ANTIQUE



HEATHER




NATURAL RED




[www.elliotts.uk.com](http://www.elliotts.uk.com)


# S P E C I F I C A T I O N S



Half Round Ridge



Eave Top Tile



Tile & Half



90° External Angle  
L/H & R/H




90° Internal Angle  
L/H & R/H




Valley Tile



Bonnet Hip



Angle Ridge



Hogs Back Ridge



Arris Hip

## C.O.S.H.H.

The control of substances Hazardous to Health. No harmful substances are added during the manufacturing process, but protective eyewear should be worn and all reasonable precautions taken to avoid inhaling dust when cutting tiles.

## Strength

Average transverse strength is 890N, well in excess of 780N which is the minimum requirements of BS402; Part 1.

## Water Absorption

Maximum permitted water absorption rate to comply with BS402; Part 1 is 10.50% Under test Vichy were found to possess an average water absorption of only 4.80%.

## Frost

Conforms to BS402; PART 1 1990 for resistance to frost damage. Vichy tiles are guaranteed by the manufacturer for 30 years, providing they are fixed in accordance with British Standard Codes of Practice.

## Fire

Vichy Tiles are non-combustible.

*Information quoted in this leaflet is correct at the time of printing but is liable to alteration without notice.*

*The reproduction of colours is subject to the limitations of the printing process. Please refer to a sample tile for exact colour reference.*

***Elliotts are leading suppliers of roofing products and are the exclusive distributor of Vichy Tiles and accessories in the UK.***



Millbank Wharf, Northam, Southampton SO14 5AG Tel: 023 8063 3833 Email: [southampton@elliott-brothers.co.uk](mailto:southampton@elliott-brothers.co.uk)

Rushington Business Park, Chapel Lane, Totton, Hampshire SO40 9AH Tel: 023 8067 5000 Email: [totton@elliott-brothers.co.uk](mailto:totton@elliott-brothers.co.uk)